

# GX 9" & 12" – Window / Surface Wall Fans

## Key Features

<b>Application:</b>	Pubs, restaurants, offices, kitchens, factories, schools & shops.
<b>Control options:</b>	for 9" & 12"
<b>Humidity:</b>	XRH controller
<b>Movement:</b>	XPIRA
<b>Speed:</b>	FR22/30 single fan (2 speeds) EC6 group controller (variable speed)
<b>Time delay:</b>	DT20

## XPELAIR GX9 and GX12

Both the GX9 and GX12 models are reversible and feature a totally enclosed external rotor motor providing constant volume outputs, even in gusty weather.

Pre-balanced impellers eliminate "fan judder" and ensure quiet, trouble-free operation. Sealed for life, maintenance free bearings ensure suitability for running at any angle. Running costs are impressively low, and when not in use the silent electro-thermal shutter closes silently against backdraughts.

A tamper-proof positive plug and socket assembly provides a means of isolation for service access.

Installation in a 25mm window or panel using standard metal ladder strips.

If installed in panels or walls thicker than 25mm, then use GXL20/50 extended ladder strips to enable connection of outer grille to inside of fan (3 for GX9 and 4 for GX12).

All models are and suitable for 220V-240V 50Hz mains operation.

Class B insulation for operation in ambient temperatures up to 40°C and are fitted with a thermal cut out.

## Specifications

	GX9	GXC9	GX12
UK reference number:	89994AW	89995AW	90012AW
Remote switch (supplied separately):	X	-	X
Integral pullcord:	-	X	-
Extract performance (m³/h) high:	636	520	1546
Extract performance (m³/h) low:	546	-	1091
Extract performance (l/s) high:	171	145	429
Extract performance (l/s) low:	151	-	303
Hole diameter (mm) window mount:	257	257	324
Hole diameter (mm) wall mount:	266	266	330
Sound pressure level (dB (A)@3m) high:	50	44	55
Electrical power rating (W):	41	32	85
Weight (kg):	4	4	7.9

# GX Range - Window / Surface Wall Fans

## Differences In Models

### GX9 Ref. 89994AW

- Variable speed use with EC6.
- 2 Speed if used with FR22/30 controller.
- Automatic shutter.
- Intake & extract.
- Connect to light switch or separate On/Off switch.



### GXC9 Ref. 89995AW

- Single speed.
- Pullcord switches fan On/Off and opens shutter.
- Extract only.

### GX12 Ref. 90012AW


- Variable speed use with EC6.
- 2 Speed if used with FR22/30 controller.
- Connect to light switch or separate On/Off switch.
- Intake & extract.
- Automatic shutter.

## Performance



# GX Range - Window / Surface Wall Fans


## Dimensions (mm)



## Installation and Accessories

### GXC9

#### DOUBLE POLE ISOLATING SWITCH



### GX9/GX12

#### DOUBLE POLE ISOLATING SWITCH

